### **TruckMaster**<sup>®</sup>

# LEADING CHANGE

# PORTABLE DIESEL STORAGE AND DISPENSING



Available from 200-900 litres. The TruckMaster is built from high quality polyethylene providing resistance to structural damage, changing weather conditions and UV radiation. It also offers a number of equipment options to suit all types of user.

#### Quality Design and Reliability

Offering a robust and resilient product design combined with a 5 year guarantee\*, quality customer service and over 40 years' experience delivering high performing products worldwide - you know you can trust Kingspan.

#### **Excellent Return On Investment**

Lightweight, portable storage solution offering a faster and safer delivery of diesel to any point of use with model options which occupy only half a euro pallet\*\* - saving you valuable time and money.



#### Portability

The TruckMaster is designed to go anywhere and to withstand toughest of site conditions offering liquid delivery a new mobility. The TuckMaster 430 and 900 litres features an internal baffle wall minimising the movement of liquid hence making the truck and the load more stable when in transit.



The 430 & 900 litre TruckMaster has been tested to meet the requirements of the European agreement (ADR) for the International Carriage of Dangerous Goods by Road\*\*\*.



\* With 1 year on equipment.

\*\* The new TruckMaster 200 and 300 litres occupy only half a euro pallet.

\*\*\* TruckMaster 200 and 300 litres do not require ADR approval due to their smaller capacity.

www.kingspantitan.com



## **TruckMaster**<sup>®</sup>

#### SPECIFICATION SELECTOR

DESCRIPTION / CAPACITY	TM200 NEW SHAPE	TM300 NEW SHAPE	тм200	ТМ430	ТМ900
Level gauge				•	•
Ball valve on suction line				•	•
Suction line with mesh filter		•	•	•	•
12 V DC pump (max. flow rate 50 l/min)		•	•	•	•
6 m power cable with battery clamps	•	•	•	•	•
4 m flexible delivery hose			•	•	
3,7 m flexible delivery hose	•	•			
Automatic nozzle	•		•	•	•
Lid with integrated lock			•	•	•
Lid with separate lock (lock not provided)	•				
Vacuum and pressure relief valve (VENT)	•	•	•	•	•
Lid with support gas struts					•
4 lifting shackles			0	•	•
Battery powered LED lamp			0	•	•
24 V DC pump (max. flow rate 50 l/min)	0	0		0	0
12/24 DC pump (max. flow rate 70/35 l/min)				0	0
12 V DC pump (max. flow rate 85 l/min)				0	0
230 V AC pump (max. flow rate 56 l/min)				0	0
Digital flowmeter fixed to the nozzle	0	0	0	0	0
Digital flowmeter fixed to the pump				0	0
	0	0	0		

• Standard accessories O Optional accessories.

#### **NEW TM 200**



Capacity 200 litres Length 600mm Width 800mm Height 620mm



Capacity 300 litres Length 600mm Width 800mm Height 890mm



TM 200



Capacity 200 litres Length 1180mm Width 860mm Height 500mm





Capacity 430 litres Length 1180mm Width 860mm Height 910mm



430



TM 900

Capacity 900 litres Length 1410mm Width 1050mm Height 1210mm

#### Equipment specification:

- 1. Tank
- Pump
  Automatic nozzle
- Automatic nozzi
  Vont
- Vent
  Delivery hose
- beilvery hose
  Lockable lid\*
- Zockable lic
  Shackles\*\*
- 8. 4" Inspection lid\*\*
- 9. Filling offset\*\*

\* Lid with integrated lock (TM200, TM430 and TM900) TM200 & TM300 can be locked with the padlock (padlock not provided). \*\* Only available on certain models.

www.kingspantitan.com